

Chlorinated Rubber Paint

DESCRIPTION:	A premium quality swimming pool paint based on pure chlorinated rubber. It is quick drying and easy to apply. Provides hardwearing and durable finish, which can be easily cleaned. The product has excellent resistance to acids, chlorine, oxidizing and bleaching agents.
SCOPE:	Though mainly designed for swimming pools, the product can also be used for the protection of concrete and primed steel in heavy traffic areas.
COMPOSITION:	Chlorinated Rubber Based. Dry film is non-toxic and lead free.
FINISH:	Low Sheen
COLOUR RANGE:	White, Blue
DRYING TIME	Touch dry – About 30 minutes. Hard dry – 12 to 14 hours. Recoatable – After 16 hours. (Checked at 25 °C and relative humidity not more than 60%.) Cooler temperature, higher film thickness or higher humidity conditions will require longer drying time. Allow the paint to dry for minimum 48 hours before filling the water.
SPECIFIC GRAVITY:	1.27 ± 0.02 Kgs/ L
% VOLUME SOLIDS:	35 ± 2
SPREADING RATE:	8 - 10m ² /L (depending on surface condition and absorbency)
THINNER / CLEAN UP:	Berger Thinner for Chlorinated Rubber Paint. Clean the equipment immediately after use.
FLASH POINT:	< 25°C, Highly flammable.
PACK SIZES:	5 Litres
APPLICATION:	<ul style="list-style-type: none">• Brush, Airless spray. (Roller application leads to bubble formation). Use recommended thinner for ease of application depending on the application method. The weather conditions will also demand for thinner for ease of application.• Stir the content thoroughly using a broad paddle. On a bare concrete and cement render, apply first coat with 20 – 30% dilution to seal the surface. Follow with two full coats. Ensure minimum 16 hours recoating interval.• In case of repainting, ensure the adhesion of old paint and then only apply one or two full coats. Poor adhesion of old paint will lead to failure of new coats.

- Always use recommended thinner for dilution and cleaning.
- Do not apply when humidity exceeds 80% and condensation is likely. Do not apply when temperature is below 10°C and more than 30°C and in windy condition.
- Allow the paint to dry fully. Forced ventilation necessary in cold conditions.
- Ensure adequate ventilation during application and drying
- Do not apply thick coat. Apply two thin coats wherever required.

SURFACE PREPARATION:

- Surface to be painted must be clean and sound. The surface should be rough enough to enable good adhesion. The contaminants like body grease, sustained lotions, oil etc. should be completely removed. Ensure the complete evaporation of chemicals/solvents used for cleaning. Ensure the removal of waxy/silicone cleaners.
- New concrete surface must be fully cured for minimum 4 weeks. If painting over old and fully cured chlorinated rubber, this product can be applied directly after proper cleaning.
- The surface should be free from dew and dampness before and during drying.

STORAGE:

Store in cool, dry condition away from direct sunlight.

DISPOSAL:

Dispose as normal paint. In case of doubt, consult local authority.
Do not empty into drains, sewers or other watercourses.

SHELF LIFE:

2 Years, when stored in original conditions.

SAFETY PRECAUTIONS:

- Allow the paint to dry for minimum 10 days before filling the water, if painted during winter season minimum 14 days curing is recommended before filling the water.
- Ensure the sealing of pool from outside. Improper sealing of pool from outside will cause water seepage, which will cause adhesion failure resulting into blisters.

FIRST AID:

Ensure adequate ventilation in confined areas where the product is being applied.
Avoid contact with skin and eyes. Wear suitable protective equipments such as overalls, goggles, dust mask and gloves. Use barrier cream for hands. Do not breathe spray mist.

EYES

In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

SKIN

Wash skin thoroughly with soap and water or approved industrial cleaner.

INHALATION

Remove into fresh air, loosen collar, and avoid excessive exertion.

INGESTION

In case of accidental ingestion, **DO NOT INDUCE VOMITING.**

Obtain immediate medical attention.

DISCLAIMER:

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.



Manufactured by BERGER PAINTS (MALTA) LTD.
HF66, INDUSTRIAL ESTATE, HAL FAR BGG 06
MALTA - EUROPE
TEL: +356 2165 8855 / +356 2165 2996
FAX: +356 2165 9409
EMAIL: info@berger.com.mt
WEBSITE: www.berger.com.mt