

Berger Dualcote

DESCRIPTION: Vinyl Acrylate Terpolymer based product to take care of damp, arising through surfaces and thus protecting the topcoats.

SCOPE: Quick drying pigmented damp sealer for use on new/old plaster, concrete and all masonry surfaces. Dualcote provides excellent adhering barrier coat to damp patches that appear on ceiling and walls.

COMPOSITION: Vinyl Acrylate Terpolymer based, Lead Free.

FINISH: Matt

COLOUR: White

DRYING TIME: Surface dry – 2 hours. Hard dry – 12 hours. Recoatable after 12 hours.
Checked at 25 °C and relative humidity not more than 75%.

SPECIFIC GRAVITY: 1.30 ± 0.02 Kgs/L

% VOLUME SOLIDS: 37 ± 2

SPREADING RATE: 4 – 6 m² / Litre, (Depend on surface condition and absorbency)

THINNER / CLEAN UP: White Spirit. After use, clean equipment immediately with White Spirit.

FLASH POINT: 37° C

PACK SIZE: 2.5 Litres, 1 Litre

APPLICATION: Brush, spray or mohair roller.
Stir well. Apply a liberal coat to the surface and allow it to dry.
Can be thin with white spirit for the ease of application.

Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Only apply when surface temperature is 3°C or more above dew point.

SURFACE PREPERATION: Ensure surfaces to be painted are sound, clean, free of grease and loose matter. The product can be applied to damp surfaces but not to saturated surfaces. Fungus affected areas must be treated with Murisan Anti-Moffa Solution and allowed to dry before painting.

STORAGE: Store in cool, dry condition away from direct sunlight.

DISPOSAL: Dispose as normal paint. In case of doubt, consult local authority.
Do not empty into drains, sewers or other watercourses

SHELF LIFE 2 Years, when stored in original conditions.

SAFETY PRECAUTIONS Ensure adequate ventilation in confined areas where the product is being applied.
Avoid contact with skin and eyes. Wear suitable protective equipments such as overalls, goggles, dust mask and gloves. Use barrier cream for hands. Do not breathe spray mist.

FIRST AID

EYES	In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.
SKIN	Wash skin thoroughly with soap and water or approved industrial cleaner. DO NOT USE solvent or thinners.
INGESTION	In case of accidental ingestion, DO NOT INDUCE VOMITING. Obtain immediate medical attention.

DISCLAIMER:

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.



Manufactured by BERGER PAINTS (MALTA) LTD.
HF66, INDUSTRIAL ESTATE, HAL FAR BBG 06
MALTA - EUROPE
TEL: +356 2165 8855 / +356 2165 2996
FAX: +356 2165 9409
EMAIL: info@berger.com.mt
WEBSITE: www.berger.com.mt